



NOTES:

1. Driveway permits shall address elevation differences that could exist at property line.
 - 1.1. drainage cannot discharge to adjacent property.
 - 1.2. curbing may be required to address drainage & differences in elevation.
 - 1.3. ensure that notes are added to permit plans if lacking proper data.
2. Concrete drive apron & sidewalk within right-of-way shall be minimum 5-1/2" true measure depth minimum.
 - 2.1. No pavers for sidewalk, unless approved by Town Engineer.
3. See Detail 108d for sidewalk interface.
4. See Detail 108c & 108d for asphalt, concrete, or paver brick typical sections and specifications.
5. Town of Jupiter Ord. 32-91 requires turnouts be located a minimum of 30' setback from intersecting roads or street rights of way.
6. Lot Width Right-of-Way Frontage Restrictions:
 - 6.1. Less than 75'; Maximum combined driveway width for 2 drives shall be 20', with a minimum individual drive width of 9'.
 - 6.2. 75' or more; Maximum individual drive width shall be 20' and maximum combined driveway width for 2 drives shall be 32'.

DOUBLE DRIVEWAY



TOWN OF JUPITER
ENGINEERING DIVISION
 210 MILITARY TRAIL
 JUPITER, FLORIDA 33458
 (561) 746-5134

RESIDENTIAL DRIVEWAYS
 DETAIL AND REQUIREMENTS

K:\Drawings\Details\2015\108 201507updates\108b - driveways.dwg

DETAIL NUMBER

108b

Revised 20150723